


Self-Lubricating Sintered Bearings
STANDARD DIMENSIONS



SELFOL®

SELFOLI® BEARINGS: STANDARD DIMENSIONS IN BRONZE



Type A Cylindrical

Diameter before fitting (mm)		L = Lengths (mm) Tolerance js13	Quantity per bag
d = Ø inner Tolerance G7	D = Ø outer Tolerance s7		
2 + 12	5 + 31	2 - 3	25
2 + 2	5 + 19		
3 + 12	6 + 31	4 - 5 - 6 - 10	25
3 + 2	6 + 19		
4 + 16	6 + 31	5 - 8 - 10	25
4 + 4	6 + 19		
4 + 16	7 + 38	4 - 8 - 12	25
4 + 4	7 + 23		
4 + 16	8 + 38	4 - 5 - 6 - 8 - 10 - 12	25
4 + 4	8 + 23		
5 + 16	8 + 38	5 - 8 - 10 - 12 - 15 - 16	25
5 + 4	8 + 23		
5 + 16	9 + 38	4 - 5 - 8	25
5 + 4	9 + 23		
5 + 16	10 + 38	5 - 6 - 8 - 10 - 12 - 15	25
5 + 4	10 + 23		
6 + 16	9 + 38	4 - 6 - 10 - 12 - 16	25
6 + 4	9 + 23		
6 + 16	10 + 38	4 - 5 - 6 - 10 - 12 - 15 - 16	25
6 + 4	10 + 23		
6 + 16	12 + 46	5 - 6 - 8 - 10 - 12 - 15 - 16	25
6 + 4	12 + 28		
7 + 20	10 + 38	5 - 8 - 10	25
7 + 5	10 + 23		
8 + 20	10 + 38	6 - 10 - 15	25
8 + 5	10 + 23		
8 + 20	11 + 28	6 - 8 - 12 - 16 - 20	25
8 + 5	11 + 23		
8 + 20	12 + 46	6 - 8 - 10 - 12 - 15 - 16 - 20	25
8 + 5	12 + 28		
8 + 20	14 + 46	8 - 10 - 12 - 15 - 16 - 20	25
8 + 5	14 + 28		
9 + 20	12 + 46	6 - 10 - 14	25
9 + 5	12 + 28		
9 + 20	14 + 46	10 - 12 - 15 - 20	25
9 + 5	14 + 28		
10 + 20	13 + 46	10 - 12 - 15 - 16 - 20 - 25	25
10 + 5	13 + 28		
10 + 20	14 + 46	8 - 10 - 16 - 20 - 25	25
10 + 5	14 + 28		
10 + 20	15 + 46	10 - 12 - 15 - 16 - 20 - 25	10
10 + 5	15 + 28		
10 + 20	16 + 46	8 - 10 - 12 - 15 - 16 - 20 - 25	10
10 + 5	16 + 28		
10 + 20	18 + 46	10 - 12 - 15 - 20 - 25	10
10 + 5	18 + 28		
12 + 24	14 + 46	10 - 12 - 15 - 20	10
12 + 6	14 + 28		
12 + 24	15 + 46	10 - 12 - 15 - 16 - 20 - 25	10
12 + 6	15 + 28		
12 + 24	16 + 46	8 - 10 - 12 - 15 - 16 - 20 - 25 - 25	10
12 + 6	16 + 28		
12 + 24	17 + 46	12 - 15 - 16 - 20 - 25	10
12 + 6	17 + 28		
12 + 24	18 + 46	8 - 10 - 12 - 15 - 16 - 20 - 25 - 30	10
12 + 6	18 + 28		
12 + 24	20 + 56	12 - 15 - 20 - 25 - 30	10
12 + 6	20 + 35		
14 + 24	18 + 46	10 - 14 - 15 - 18 - 20 - 22 - 25 - 28	10
14 + 6	18 + 28		
14 + 24	20 + 56	10 - 12 - 14 - 15 - 18 - 20 - 22 - 25 - 28 - 30	10
14 + 6	20 + 35		
14 + 24	22 + 56	15 - 20 - 25 - 30	10
14 + 6	22 + 35		
15 + 24	18 + 46	15 - 20 - 25 - 30	10
15 + 6	18 + 28		
15 + 24	19 + 56	10 - 15 - 16 - 20 - 25 - 32	10
15 + 6	19 + 35		
15 + 24	20 + 56	10 - 12 - 15 - 20 - 25 - 30	10
15 + 6	20 + 35		
15 + 24	21 + 56	10 - 15 - 16 - 20 - 25 - 32	10
15 + 6	21 + 35		
15 + 24	22 + 56	15 - 16 - 20 - 25 - 30	10
15 + 6	22 + 35		
16 + 24	20 + 56	12 - 15 - 16 - 20 - 25 - 30 - 32	10
16 + 6	20 + 35		
16 + 24	22 + 56	12 - 15 - 16 - 20 - 25 - 30 - 32 - 35	10
16 + 6	22 + 35		
17 + 24	22 + 56	15 - 20 - 25 - 30 - 35	10
17 + 6	22 + 35		
18 + 24	22 + 56	12 - 15 - 18 - 20 - 22 - 25 - 28 - 30 - 36	10
18 + 6	22 + 35		
18 + 24	24 + 56	12 - 18 - 22 - 28 - 30 - 36	10
18 + 6	24 + 35		
18 + 24	25 + 56	16 - 18 - 20 - 22 - 25 - 28 - 30 - 35 - 36	10
18 + 6	25 + 35		

Tolerances in µm


Run-out: IT-9 for D≤ 50 and IT-10 for D>50

Designation (reference for orders)

A cylindrical bronze bearing of 25 mm inner diameter, 30 mm outer diameter and 35 mm length, is designated as:

SELFOLI® Bearing A-25-30-35

(letter A indicates bronze cylindrical bearing)




Type A Cylindrical

Diameter before fitting (mm) d = Ø inner Tolerance G7	D = Ø outer Tolerance s7	L = Lengths (mm) Tolerance js13	Quantity per bag
20 + 28	24 + 56	16 - 20 - 25 - 32	10
20 + 28	25 + 56	15 - 16 - 20 - 25 - 30 - 32 - 35	10
20 + 28	26 + 56	15 - 16 - 20 - 25 - 30 - 32 - 35 - 40	10
20 + 28	27 + 56	16 - 20 - 25 - 32	10
20 + 28	28 + 56	16 - 20 - 25 - 30 - 32 - 35 - 40	10
20 + 28	30 + 56	20 - 25 - 30 - 35 - 40	10
22 + 28	27 + 56	15 - 18 - 20 - 22 - 25 - 28 - 30 - 35 - 36 - 40	10
22 + 28	28 + 56	18 - 20 - 22 - 25 - 28 - 30 - 35 - 36 - 40	10
22 + 28	29 + 56	18 - 22 - 28 - 36	10
25 + 28	30 + 56	20 - 25 - 30 - 32 - 35 - 40	10
25 + 28	32 + 68	20 - 25 - 30 - 32 - 35 - 40 - 45	10
25 + 28	35 + 68	25 - 30 - 35 - 40 - 45 - 50	5
28 + 28	32 + 68	20 - 22 - 25 - 28 - 32 - 36 - 40	5
28 + 28	33 + 68	20 - 22 - 25 - 28 - 32 - 36 - 40 - 45	5
28 + 28	35 + 68	25 - 30 - 35 - 40 - 45 - 50	5
28 + 28	36 + 68	22 - 28 - 36 - 45	5
30 + 28	35 + 68	20 - 25 - 30 - 35 - 40 - 45 - 50	5
30 + 28	38 + 68	20 - 24 - 25 - 30 - 35 - 38 - 40 - 45 - 50	5
30 + 28	40 + 68	20 - 25 - 30 - 35 - 40 - 45 - 50	5
32 + 34	38 + 68	20 - 25 - 32 - 40 - 50	5
32 + 34	40 + 68	20 - 25 - 30 - 32 - 35 - 40 - 45 - 50	5
35 + 34	40 + 68	20 - 25 - 30 - 35 - 40 - 45 - 50	5
35 + 34	41 + 68	25 - 35 - 40	5
35 + 34	44 + 68	22 - 28 - 35	5
35 + 34	45 + 68	25 - 30 - 35 - 40 - 45 - 50 - 60	5
36 + 34	42 + 68	22 - 28 - 36 - 45	5
36 + 34	45 + 68	22 - 28 - 36 - 45	5
38 + 34	44 + 68	25 - 35 - 45	5
40 + 34	45 + 68	35 - 40 - 45 - 50	5
40 + 34	46 + 68	25 - 30 - 32 - 40 - 50	5
40 + 34	50 + 68	25 - 32 - 40 - 45 - 50 - 60	5
45 + 34	51 + 83	28 - 36 - 45 - 56	5
45 + 34	55 + 83	30 - 35 - 40 - 45 - 50 - 55 - 60	5
45 + 34	56 + 83	28 - 36 - 45 - 56	5
45 + 34	60 + 83	40 - 45 - 50 - 60	2
50 + 34	56 + 83	32 - 40 - 50 - 63	2
50 + 34	60 + 83	32 - 40 - 45 - 50 - 60 - 63 - 70 - 100	2
55 + 40	65 + 83	40 - 55 - 70	2
60 + 40	70 + 89	50 - 60 - 90 - 120	2
60 + 40	72 + 89	50 - 60 - 70	1
60 + 40	80 + 89	90 - 120	1
63 + 40	70 + 89	40 - 50	1
70 + 40	80 + 89	90 - 120	1
80 + 56 (G8)	95 + 125 (s8)	70 - 80 - 90	1
80 + 56 (G8)	100 + 125 (s8)	80 - 120	1
100 + 66 (G8)	120 + 133 (s8)	80 - 120	1

SELFOLI® High Performance characteristics: see page 9

Tolerance in µm / Run-out: IT-9 for D≤ 50 and IT-10 for D>50



Designation (reference for orders)

A cylindrical bronze bearing with flange of 16 mm inner diameter, 20 mm outer diameter and 25 mm length, is designated as:

SELFOIL® Bearing B-16-20-25/24-2


(letter B indicates bronze cylindrical bearing with flange, and values 24-2 correspond to the flange diameter and thickness)

Type B Flanged

Diameter before fitting (mm)		L = Lengths (mm) Tolerance js13	Flange (mm)		Quantity per bag
d = Ø inner Tolerance G8	D = Ø outer Tolerance s8		D' = Ø Flange Tolerance js13	e = Thickness Tolerance js14	
3 + 2	6 + 37	4 - 5 - 6 - 10	9	1,5	25
4 + 22	8 + 45	4 - 5 - 8 - 10 - 12	12	2	25
6 + 22	10 + 45	6 - 10 - 15 - 16	14	2	25
8 + 27	12 + 55	8 - 10 - 12 - 15 - 16	16	2	25
9 + 27	14 + 55	6 - 10 - 14	19	2,5	10
10 + 27	13 + 55	10 - 16 - 20	16	1,5	10
10 + 27	14 + 55	10 - 15 - 20	18	2	10
10 + 27	15 + 55	10 - 15 - 16 - 20	20	3	10
10 + 27	16 + 55	8 - 10 - 16	22	3	10
12 + 33	15 + 55	12 - 16 - 20	18	1,5	10
12 + 33	17 + 55	10 - 12 - 15 - 16 - 20 - 25	22	3	10
12 + 33	18 + 55	8 - 12 - 20	24	3	10
14 + 33	18 + 55	14 - 18 - 22	22	2	10
14 + 33	20 + 68	14 - 15 - 18 - 20 - 22 - 25 - 28 - 30	25	3	10
15 + 33	19 + 68	16 - 20 - 25	23	2	10
15 + 33	20 + 68	15 - 20 - 25 - 30	25	3	10
15 + 33	21 + 68	16 - 20 - 25 - 32	27	3	10
16 + 33	20 + 68	16 - 20 - 25	24	2	10
16 + 33	22 + 68	15 - 16 - 20 - 25 - 30 - 32	28	3	10
18 + 33	22 + 68	18 - 22 - 28	26	2	10
18 + 33	24 + 68	18 - 22 - 28	30	3	10
18 + 33	25 + 68	20 - 25 - 30 - 35	32	4	10
20 + 40	24 + 68	10 - 16 - 20 - 25	28	2	10
20 + 40	26 + 68	15 - 16 - 20 - 25 - 30 - 32	32	3	10
20 + 40	28 + 68	20 - 25 - 30 - 35	35	4	10
22 + 40	27 + 68	18 - 22 - 28	32	2,5	10
22 + 40	28 + 68	15 - 20 - 25 - 30 - 35 - 40	33	4	10
22 + 40	29 + 68	18 - 22 - 28 - 36	36	3,5	10
25 + 40	30 + 68	20 - 25 - 32	35	2,5	10
25 + 40	32 + 82	20 - 25 - 30 - 32 - 35 - 40	40	4	10
25 + 40	35 + 82	16 - 25 - 30	45	5	10
28 + 40	33 + 82	22 - 28 - 36	38	2,5	10
28 + 40	36 + 82	22 - 25 - 28 - 30 - 35 - 36 - 40	44	4	10
30 + 40	38 + 82	20 - 25 - 30	46	4	10
30 + 40	40 + 82	25 - 30 - 35 - 40	48	4	10
32 + 48	38 + 82	20 - 25 - 32	44	3	10
32 + 48	40 + 82	20 - 25 - 30 - 32 - 35 - 40	48	4	10
35 + 48	45 + 82	20 - 25 - 30 - 35 - 40	55	5	10
36 + 48	42 + 82	22 - 28 - 36	48	3	10
36 + 48	45 + 82	22 - 28 - 36	54	4,5	10
40 + 48	46 + 82	25 - 32 - 40	52	3	5
40 + 48	50 + 82	25 - 30 - 32 - 35 - 40	60	5	5
45 + 48	51 + 99	28 - 36 - 45	57	3	5
45 + 48	56 + 99	28 - 36 - 45	67	5,5	5
50 + 48	56 + 99	32 - 40 - 50	62	3	5
50 + 48	60 + 99	32 - 40 - 50	70	5	5
60 + 56	70 + 105	50 - 60	80	5	5

SELFOIL® High Performance characteristics: see page 9

Tolerance in µm / Run-out: IT-9 for D≤ 50 and IT-10 for D>50



Designation (reference for orders)

A spherical bronze bearing of 10 mm inner diameter, 22 mm sphere diameter and 16 mm length, is designated as:


SELFOLI® Bearing C-10-22-16

(letter C indicates spherical bearing)

Type C Spherical

$d = \text{Ø inner}$ Tolerance H7	$E = \text{Ø sphere (mm)}$ Tolerance ± 0.05	$L = \text{Lengths (mm)}$ Tolerance ± 0.15	Quantity per bag
4	10	8	25
5	12	9	25
6	14	11	25
7	16	12	25
8	18	13	25
9	20	14,5	25
10	22	16	25
12	23	16	25

Run-out: IT-9



Designation (reference for orders)

A cylindrical bronze bearing of 1" inner diameter, 1½" outer diameter and 2" length, is designated as:

SELFOLI® Bearing A-1-1½-2


(letter A indicates bronze cylindrical bearing)

Type A Cylindrical (dimensions in inches)

Diameter before fitting (in)		$L = \text{Lengths (in)}$ Tolerance js13	Quantity per bag
$d = \text{Ø inner}$ Tolerance G7	$D = \text{Ø outer}$ Tolerance s7		
1/4	1/2	1/4 - 3/8 - 1/2 - 5/8 - 3/4	25
5/8	5/8	5/8 - 1/2 - 5/8 - 3/4 - 1	25
1/2	1 1/16	1/2 - 5/8 - 3/4 - 1 - 1 1/4	10
1/2	3/4	1/2 - 5/8 - 3/4 - 1 - 1 1/4	10
5/8	3/4	1/2 - 5/8 - 3/4 - 1 - 1 1/4	10
5/8	7/8	1/2 - 5/8 - 3/4 - 1 - 1 1/4	10
3/4	7/8	5/8 - 3/4 - 7/8 - 1 - 1 1/4	10
3/4	1	5/8 - 3/4 - 7/8 - 1 - 1 1/4	10
3/4	1 1/4	5/8 - 3/4 - 7/8 - 1 - 1 1/4	10
1	1 1/8	3/4 - 1 - 1 1/4 - 1 1/2	10
1	1 1/2	3/4 - 1 - 1 1/4 - 1 1/2	5
1 1/2	2	1 1/2 - 2 - 2 1/4 - 2 1/2	5
2	2 1/2	1 1/2 - 2 - 2 1/4 - 2 1/2	2
2 1/2	3	1 1/2 - 2 - 2 1/4 - 2 1/2	1

Run-out: IT-9 for $D \leq 2"$ and IT-10 for $D \geq 2"$

SELFOIL® BEARINGS: STANDARD DIMENSIONS IN IRON



Type AF Cylindrical

Diameter before fitting (mm)		L = Lengths (mm)	Quantity per bag
d = Ø inner Tolerance G7	D = Ø outer Tolerance s7	Tolerance js13	
3 + 12	6 + 31	4 - 10	25
4 + 16	8 + 38	8	25
6 + 16	9 + 38	6 - 10 - 12 - 16	25
6 + 16	10 + 38	6 - 10 - 16	25
6 + 16	12 + 28	6	25
8 + 20	11 + 46	8 - 12 - 16	25
8 + 20	12 + 46	8 - 12 - 16 - 20	25
10 + 20	13 + 46	10 - 20 - 25	25
10 + 20	14 + 46	10 - 16 - 20	25
10 + 20	15 + 46	10	10
12 + 24	15 + 28	12 - 16 - 20	10
12 + 24	16 + 28	12 - 16 - 20 - 25	10
12 + 24	17 + 28	12	10
14 + 24	18 + 28	14 - 22	10
14 + 24	20 + 35	14 - 28	10
15 + 24	19 + 35	16 - 20	10
16 + 24	20 + 35	16 - 20 - 25 - 32	10
16 + 24	22 + 35	16 - 20 - 25	10
18 + 24	22 + 35	18 - 22	10
18 + 24	24 + 35	22	10
20 + 28	24 + 35	16 - 20 - 25 - 32	10
20 + 28	26 + 35	16 - 20 - 25 - 32	10
22 + 28	27 + 35	18 - 22	10
25 + 28	30 + 35	20 - 25 - 32	10
25 + 28	32 + 43	20 - 25 - 32	10
30 + 28	38 + 43	24 - 30 - 38	5
32 + 34	38 + 43	32	5
35 + 34	44 + 43	22 - 28 - 35	5
36 + 34	42 + 43	22	5
40 + 34	46 + 43	25 - 32 - 40	5
40 + 34	50 + 43	25 - 32 - 40 - 50	5
45 + 34	51 + 53	28 - 45	5
45 + 34	55 + 53	35	5
45 + 34	56 + 53	36	5
50 + 34	56 + 53	32	2
50 + 34	60 + 53	32 - 50	2
60 + 40	70 + 59	60 - 90	2
70 + 40	80 + 59	120	1
80 + 56 (G8)	100 + 125 (s8)	120	1
100 + 66	120 + 133 (s8)	120	1
100 + 12 (G8)			


Tolerance in μm / Run-out: IT-9 for $D \leq 50$ and IT-10 for $D > 50$
 SELFOIL® High Performance characteristics: see page 9

Designation (reference for orders)

A cylindrical iron bearing of 25 mm inner diameter, 30 mm outer diameter and 32 mm length, is designated as:

SELFOIL® Bearing AF-25-30-32

(letters AF indicate iron cylindrical bearing)



Designation (reference for orders)

A cylindrical iron bearing with flange of 16 mm inner diameter, 22 mm outer diameter and 25 mm length, is designated as:

SELFOIL® Bearing BF-16-22-25/28-3

(letters BF indicate iron cylindrical bearing with flange, values 28-3 correspond to the flange diameter and thickness)

Type BF Flanged

Diameter before fitting (mm)		L = Lengths (mm) Tolerance js13	Flange (mm)		Quantity per bag
d = Ø inner Tolerance G8	D = Ø outer Tolerance s8		D' = Ø Flange Tolerance js13	e = Thickness Tolerance js14	
3 + 16	6 + 37	4	9	1,5	25
6 + 22	10 + 45	6 - 10 - 16	14	2	25
8 + 27	12 + 55	8 - 12 - 16	16	2	25
10 + 27	13 + 55	10 - 16	16	1,5	10
10 + 27	15 + 55	10 - 16 - 20	20	2,5	10
12 + 33	15 + 55	12 - 16 - 20	18	1,5	10
12 + 33	17 + 55	12 - 16	22	2,5	10
14 + 33	18 + 55	14 - 18 - 22	22	2	10
16 + 33	20 + 68	16 - 20	24	2	10
16 + 33	22 + 68	16 - 20 - 25	28	3	10
18 + 33	24 + 68	18 - 22	30	3	10
20 + 40	24 + 68	16 - 20 - 25	28	2	10
20 + 40	26 + 68	16 - 20 - 25	32	3	10
22 + 40	29 + 68	18 - 22 - 28 - 36	36	3,5	10
25 + 40	30 + 68	20 - 32	35	2,5	10
25 + 40	32 + 82	25 - 32	39	3,5	10
SELFOIL® HIGH PERFORMANCE	30 + 40	38 + 82	30	4	10
	32 + 48	40 + 82	20 - 32	4	10
	36 + 48	45 + 82	22 - 36	4,5	10
	40 + 48	50 + 82	25 - 32 - 40	5	5
	50 + 48	60 + 99	50	5	5
	60 + 56	70 + 105	60	5	5

Tolerance in μm

Run-out: IT-9 for $D \leq 50$ and IT-10 for $D > 50$

SELFOIL® High Performance characteristics: see page 9



SELFOIL® RODS FOR MACHINING: STANDARD DIMENSIONS



Type T Machining Rods in Bronze

Solid		
D = Ø outer (mm)	L = Lengths (mm)	Quantity per bag
15 ±0.8	30 min.	5
20 ±0.8	25 min.	5
20 ±0.8	50 min.	2
25 ±0.8	25 min.	2
25 ±0.8	50 min.	2
32 ±0.8	40 min.	2
32 ±0.8	80 min.	1
42 ±0.8	50 min.	1
42 ±0.8	100 min.	1
45 ± 1	90 min.	1
52 ± 1	60 min.	1
52 ± 1	120 min.	1
62 ±1.5	120 min.	1
70 ±1.5	120 min.	1
80 ±1.5	120 min.	1
105 ± 2	120 min.	1
125 min.	80 min.	1
125 min.	140 min.	1
149 min.	80 min.	1
149 min.	140 min.	1
178 min.	140 min.	1
202 min.	80 min.	1

Hollow			
d = Ø inner (mm)	D = Ø outer (mm)	L = Lengths (mm)	Quantity per bag
38 ± 0.8	66 ±1.5	65 min.	1
38 ± 0.8	66 ±1.5	120 min.	1
45 ± 0.8	105 ±1.5	120 min.	1
53 ± 1	85 ±1.5	65 min.	1
53 ± 1	85 ±1.5	120 min.	1
68 ± 1.5	104 ±1.5	65 min.	1
68 ± 1.5	104 ±1.5	120 min.	1
83 ± 1.5	123 ±2	65 min.	1
83 ± 1.5	123 ±2	120 min.	1
98 ± 1.5	142 ±2	65 min.	1
98 ± 1.5	142 ±2	120 min.	1
59 max.	125 min.	80 min.	1
59 max.	125 min.	140 min.	1
79 max.	149 min.	80 min.	1
79 max.	149 min.	140 min.	1
110 max.	178 min.	80 min.	1
110 max.	178 min.	140 min.	1
150 max.	202 min.	140 min.	1

Type TF Machining Rods in Iron

Solid		
D = Ø outer (mm)	L = Lengths (mm)	Quantity per bag
15 ± 1	30 ± 2	5
20 ± 1	25 ± 2	5
20 ± 1	50 ± 2	2
25 ± 1	25 ± 2	2
25 ± 1	50 ± 2	2
32 ± 1	40 ± 2	2
32 ± 1	80 ± 2	1
42 ± 1	50 ± 2	1
42 ± 1	100 ± 2	1
45 ± 1	90 ± 2	1
52 ± 1	60 ± 2	1
52 ± 1	120 ± 2	1
62 ± 1	120 ± 2	1
70 ± 1	120 ± 2	1
80 ± 1	120 ± 2	1

Hollow			
d = Ø inner (mm)	D = Ø outer (mm)	L = Lengths (mm)	Quantity per bag
38 ± 1	66 ±1.5	65 ±2	1
38 ± 1	66 ±1.5	120 ±2	1
53 ± 1	85 ±1.5	65 ±2	1
53 ± 1	85 ±1.5	120 ±2	1

Designation (reference for orders)

A solid bronze rod of 25 mm diameter and 50 mm length is designated as:

SELFOIL® Rod T-25-50

(letter T indicates bronze rod for machining)

Designation (reference for orders)

A hollow iron rod of 38 mm inner diameter, 55 mm outer diameter and 120 mm length, is designated as:

SELFOIL® Rod TF-38-66-120

(letters TF indicate iron rod for machining)

Tolerances in mm.

We recommend machining by following the conditions indicated on page 17. Impregnation with Ames-01oil after machining is encouraged.